



Specifications | HBT Hubs

Front Hubs HBT						
Model Name	HBT30 Front		HBT30 Rear			
Model No. (Alloy Silver)	HBT30.F0AB.AA0	HBT30.F0AC.AA0	HBT30.RRAB.AA0	HBT30.RRAC.AA0	HBT30.RSAB.AA0	HBT30.RSAC.AA0
Model No. (Black)	HBT30.F0AB.BA0	HBT30.F0AC.BA0	HBT30.RRAB.BA0	HBT30.RRAC.BA0	HBT30.RSAB.BA0	HBT30.RSAC.BA0
Model No. (Gold)	HBT30.F0AB.GA0	HBT30.F0AC.GA0	HBT30.RRAB.GA0	HBT30.RRAC.GA0	HBT30.RSAB.GA0	HBT30.RSAC.GA0
Model No. (Red)	HBT30.F0AB.RA0	HBT30.F0AC.RA0	HBT30.RRAB.RA0	HBT30.RRAC.RA0	HBT30.RSAB.RA0	HBT30.RSAC.RA0
Model No. (Blue)	HBT30.F0AB.2A0	HBT30.F0AC.2A0	HBT30.RRAB.2A0	HBT30.RRAC.2A0	HBT30.RSAB.2A0	HBT30.RSAC.2A0
Hub Shell Material	6061 Aluminum		6061 Aluminum		6061 Aluminum	
Bearing	Sealed Cartridge		Sealed Cartridge		Sealed Cartridge	
Axle Material	Chromoly		Chromoly		Chromoly	
Axle Diameter	9mm		10mm		10mm	
Axle Length	145mm		175mm		165mm	
Over Lock Dimension	100mm		130mm		120mm	
Spoke Holes	(B) 36H	(C) 32H	(B) 36H	(C) 32H	(B) 36H	(C) 32H
Pitch Circle Diameter	61.5mm		61.5mm		61.5mm	
Flange Width	70.6mm		66.6mm		66.6mm	
Center to Flange	Right	35.3mm	33.3mm		33.3mm	
	Left	35.3mm	33.3mm		33.3mm	
Finish	Hi-Polish Anodized		Hi-Polish Anodized		Hi-Polish Anodized	
Average Weight	270g		335g		325g	



Specifications | HBT Hubs

Single Speed Freewheel		
Model Name	SFS30	
Model No. (16T)	SFS30.W160.CA0	SFS30.N160.CA0
Model No. (17T)	SFS30.W170.CA0	SFS30.N170.CA0
Model No. (18T)	SFS30.W180.CA0	SFS30.N180.CA0
Model No. (19T)	SFS30.W190.CA0	SFS30.N190.CA0
Model No. (20T)	SFS30.W200.CA0	SFS30.N200.CA0
Model No. (21T)	SFS30.W210.CA0	SFS30.N210.CA0
Model No. (22T)	SFS30.W220.CA0	SFS30.N220.CA0
Chain Size	1/2" x 1/8"	1/2" x 3/32"
Outer Body Cog	Cold Forged Steel / Chrome Plated	
Inner Body	Cold Forged Steel / Chrome Plated	
Screw Cap	Steel / Chrome Plated	
Bearing	Loose Ball	
Average Weight	194g (16T)	186g (16T)