



Specifications | Rotary 3 Speed Hubs

IGH C30				
Model Name	RX-RD3	RS-RK3	RS-RB3	RS-RF3
Model No. (36H)	IHC3T.XBSS.AA0	IHC3K.QBSS.AA0	IHC3B.QBSS.AA0	IHC3F.QBSS.AA0
Model No. (32H)	×	IHC3K.QCSS.AA0	IHC3B.QCSS.AA0	IHC3F.QCSS.AA0
Model No. (28H)	×	IHC3K.QDSS.AA0	IHC3B.QDSS.AA0	IHC3F.QDSS.AA0
Speed	3-Speed			
Type	70mm Drum Brake	Disc Brake	Band Brake	Freewheel
Hub Shell Material	A356 Aluminum	6061 Aluminum	6061 Aluminum	6061 Aluminum
Gear Ratio	Overall Range	177%		
	1	75%	(-) 25%	
	2	100%	Direct Drive	[Gear 1 (+) 33%]
	3	133%	(+) 33.3%	[Gear 2 (+) 33%]
Axle Diameter	3/8" Slotted			
Axle Length	185mm	185mm	185mm	185mm
Over Locknut Dimension	135mm	135mm	135mm	129mm
R:Axle Protusion Length	27mm	26mm	27mm	27mm
L:Axle Protusion Length	23mm	24mm	23mm	29mm
Spocke Holes	(B) 36H	(B) 36H / (C) 32H / (D) 28H	(B) 36H / (C) 32H / (D) 28H	(B) 36H / (C) 32H / (D) 28H
Pitch Circle Diameter	89.8mm	67.0mm	67.0mm	67.0mm
Flange Width	65.9mm	56.6mm	56.6mm	56.6mm
Center to Flange	Right	20.4mm	20.8mm	22.8mm
	Left	45.5mm	35.8mm	33.8mm
Spocke Compatibility	13G & 14G			
Sprocket Teeth	17T ~ 19T			
Chain Line: 3mm Deep Dished	45.6mm	43.2mm	45.2mm	41.7mm
Finish	Natural Alloy	Anodized Alloy	Anodized Alloy	Anodized Alloy
Weight	1,440g	1,095g	1,045g	990g