



Specifications | 5 Speed Hubs

IGH C50							
Model Name		RXL-RD5	RX-RD5	RX-RK5	RX-RF5		RX-RC5
Model No. (36H)		IHC5T.YBSS.AA0	IHC5T.XBSS.AA0	IHC5K.XBSS.AA0	IHC5F.XBSS.AA0	IHC5F.XBCS.AA0	IHC5C.XBSS.AA0
Model No. (32H)		×	×	IHC5K.XCSS.AA0	IHC5F.XCSS.AA0	IHC5F.XCCS.AA0	IHC5C.XCSS.AA0
Model No. (28H)		×	×	×	×	×	×
Model No. (High Polish)		IHC5T.YBSS.HA0	IHC5T.XBSS.HA0	×	×	×	×
Speed		5-Speed					
Type		90mm Drum Brake	70mm Drum Brake	Disc Brake	Freewheel		Coaster Brake
Hub Shell Material		A356 Aluminum	A356 Aluminum	6061 Aluminum	6061 Aluminum		6061 Aluminum
Gear Ratio	Overall Range	242%					
	1	64% (-) 36%					
	2	80% (-) 20% [Gear 1 (+) 25%]					
	3	100% Direct Drive [Gear 2 (+) 25%]					
	4	125% (+) 25% [Gear 3 (+) 25%]					
	5	156% (+) 56% [Gear 4 (+) 25%]					
Axle Diameter		13/32" Slotted					
Axle Length		185mm	185mm	185mm	185mm	178mm	185mm
Over Locknut Dimension		135mm	135mm	135mm	135mm	128mm	135mm
R: Axle Protrusion Length		26mm	26mm	26mm	25mm	25mm	26mm
L: Axle Protrusion Length		24mm	24mm	24mm	25mm	25mm	24mm
Spoke Holes		(B) 36H	(B) 36H	(B) 36H / (C) 32H	(B) 36H / (C) 32H		(B) 36H / (C) 32H
Pitch Circle Diameter		109mm	95.5mm	95.5mm	95.5mm	95.5mm	95.5mm



Specifications | 5 Speed Hubs

Flange Width		80.5mm	80.5mm	57.5mm	57.5mm	57.5mm	57.5mm
Center to Flange	Right	30.4mm	30.4mm	30.5mm	29.7mm	26.8mm	30.5mm
	Left	50.1mm	50.1mm	27.0mm	27.8mm	30.7mm	27.0mm
Spoke Compatibility		13G & 14G					
Sprocket Teeth		16T ~ 22T					
Chain Line: 1/8" Flat		43.9mm	43.9mm	44.0mm	43.2mm	40.3mm	44.0mm
Finish		Natural Alloy	Natural Alloy	Anodized Alloy	Anodized Alloy		Anodized Alloy
Weight		2,480g	2,290g	2,000g	1,980g	1,950g	2,400g