



Specifications | Cassette Freehub 3 Speed

IGH F30							
Model Name		CS-RK3			CS-RF3		
Model No. (Alloy Silver)		IHF3K.QBSS.AA0	IHF3K.QCSS.AA0	IHF3K.QDSS.AA0	IHF3F.QBSS.AA0	IHF3F.QCSS.AA0	IHF3F.QDSS.AA0
Model No. (Black)		IHF3K.QBSS.BA0	IHF3K.QCSS.BA0	IHF3K.QDSS.BA0	IHF3F.QBSS.BA0	IHF3F.QCSS.BA0	IHF3F.QDSS.BA0
Speed		3 x 9/8-Speed			3 x 9/8-Speed		
Type		Disc Brake Type			Freewheel		
Hub Shell Material		6061 Aluminum			6061 Aluminum		
Gear Ratio	Overall Range	177%			177%		
	1	75% (-) 25%			75% (-) 25%		
	2	100%	Direct Drive	[Gear 1 (+) 33%]	100%	Direct Drive	[Gear 1 (+) 33%]
	3	133%	(+) 33.3%	[Gear 2 (+) 33%]	133%	(+) 33.3%	[Gear 2 (+) 33%]
Axle Diameter		13/32" Slotted			13/32" Slotted		
Axle Length		179mm			179mm		
Over Locknut Dimension		135mm			135mm		
R: Axle Protrusion Length		22mm			22mm		
L: Axle Protrusion Length		22mm			22mm		
Spoke Holes		(B) 36H	(C) 32H	(D) 28H	(B) 36H	(C) 32H	(D) 28H
Pitch Circle Diameter		67.0mm			67.0mm		
Flange Width		56.6mm			56.6mm		
Center to Flange	Right	21.4mm			21.4mm		
	Left	35.4mm			35.4mm		
Spoke Compatibility		13G &14G			13G &14G		



Specifications | Cassette Freehub 3 Speed

Cassette Sprocket Type	9/8-Speed	9/8-Speed
Max. Sprocket	34T	34T
Min. Sprocket	11T	11T
Chain Line:	45mm	45mm
Indicators	MK8	MK8
Finish	Anodized Alloy	Anodized Alloy
Weight	1,155g	1,090g