



Specifications | Fixed 3 Speed

IGH S3X			
Model Name		S3X	
Model No. (Alloy Silver 36H)		IHS3X.QBSS.AA0	IHS3X.QBLS.AA0
Model No. (Alloy Silver 32H)		IHS3X.QCSS.AA0	IHS3X.QCLS.AA0
Model No. (Black 36H)		IHS3X.QBSS.BA0	IHS3X.QBLS.BA0
Model No. (Black 32H)		IHS3X.QCSS.BA0	IHS3X.QCLS.BA0
Model No. (Gold 36H)		IHS3X.QBSS.GA0	IHS3X.QBLS.GA0
Model No. (Gold 32H)		IHS3X.QCSS.GA0	IHS3X.QCLS.GA0
Model No. (Red 36H)		IHS3X.QBSS.RA0	IHS3X.QBLS.RA0
Model No. (Red 32H)		IHS3X.QCSS.RA0	IHS3X.QCLS.RA0
Model No. (Blue 36H)		IHS3X.QBSS.2A0	IHS3X.QBLS.2A0
Model No. (Blue 32H)		IHS3X.QCSS.2A0	IHS3X.QCLS.2A0
Type		Fixed Gear	
Speed		3-Speed	
Hub Shell Material		6061 Aluminum	
Gear Ratio	Overall Range	160%	
	1	62.5%	(-) 37.5%
	2	75%	(-) 25% [Gear 1 (+) 20%]
	3	100%	Direct Drive [Gear 2 (+) 33%]
Axle Diameter		13/32" Slotted	
Axle Length		165mm	174mm



Specifications | Fixed 3 Speed

Over Locknut Dimension		120mm	130mm
R: Axle Protrusion Length		22mm	21mm
L: Axle Protrusion Length		23mm	23mm
Spoke Holes		(B) 36H / (C) 32H	
Pitch Circle Diameter		67.0mm	67.0mm
Flange Width		56.6mm	56.6mm
Center to Flange	Right	24.7mm	24.0mm
	Left	31.9mm	32.6mm
Spoke Compatibility		14G	14G
Sprocket Teeth 1/8"		13~22T	13~22T
Sprocket Teeth 3/32"		12~22T	12~22T
Chain Line		42 , 43 , 44 , 45mm	42 , 43 , 44 , 45mm
Indicator		Orange	White
Finish		High Polish Anodized	
Weight		980g	990g